
Dock leveler

ASSA ABLOY DL6020T

ASSA ABLOY
Entrance Systems

The global leader in
door opening solutions



Telescopic lip dock leveler for general applications

The ASSA ABLOY DL6020T Teledock, i.e. the dock leveler with a telescopic lip, is the universal and most flexible docking system. It is suitable for every loading situation - regardless if its complexity. The main advantage compared to other levelers is the movable telescopic lip which can be precisely positioned on the vehicle bed, thus giving optimal load utilisation of the whole vehicle bed area.

The ASSA ABLOY DL6020T Teledock:
- Telescopic lip giving optimal load utilization of the whole vehicle bed area.
- Easy and comfortable operation.

The option Ergonomic Lip:
- Absolute bump free transition from the leveler platform to the lip.
- Especially designed for operations with typical electric pallet trucks without spring bumpers.


ASSA ABLOY 950 series - the intelligent, all in one, docking control system
The innovative and unique 950 series docking control system gives you direct control of the dock leveler, dock shelter and door all in one control unit. With only a few self explaining buttons it is easy to operate, to meet the demands of modern logistics. Separate steering units or complex wiring are no longer needed.

ASSA ABLOY DE6090DI Dock-IN
ASSA ABLOY Dock-IN is the world's first combined solution with parking guide and traffic lights in one system. ASSA ABLOY Dock-IN ensures a safe and secure dock in procedure with the help of white guiding lights and red traffic lights. There is no need to paint and repaint guiding lines on the asphalt or install conventional steel parking guides, which are an obstacle in the yard. With modern LED technology ASSA ABLOY Dock-IN has a low energy consumption and a long life.

Technical Data

Nominal length	2000mm, 2500 mm
Nominal width	2000mm
Load capacity	60 kN (6 tonnes)
Vertical working range Rise above dock Fall below dock	 up to 500 mm down to 370 mm
Platform tear-plate thickness	8/10 mm
Max. point load leveler platform	6,5 N / mm² (8 mm tear plate)
Lip type and length	telescopic, 1000 mm
Lip material	steel
Lip option	tapered lip / Retracting tongues
Control unit protection class	IP 54
Temperature range hydraulic oil	-30°C - +60°C
European standard	EN 1398 Dock levelers


Dimensions



NL	Nominal length
OL	Overall length
GL	Gradient length
NW	Nominal width
LE	Lip extension
LH	Leveler height
A	Working range above dock level
B	Working range below dock level

Dimensions		Vertical working range	
		60 kN	
		LE 1000	
NL	LH	A	B
2000	600	380	370
2500	600	500	290

Electrical preparations



1	Control unit (included in the delivery)	
2	Conduit for wiring internal diameter 70, angles <45° (by others)	
3	Mains supply: Mains fuse: Motor power:	3 / N / PE AC 50 Hz / 380V D0 10 A gL 1,5 kW
4	Cable:	7 x 0,75 mm²
5	Motor cable:	4 x 1,5 mm²
6	Optional safety switch on sectional door to disable leveler when door is closed*	


*Non standard


Operating functions for Tele lip levelers




TD = Teledock
L = Leveler
A = Auto Button
D = Door
S = Shelter

ASSA ABLOY DE6090DI Dock-IN







Standard available colours

Blue
RAL 5010

ASSA ABLOY, Besam, Crawford, Megadoor and Albany, as words and logos, are examples of trademarks owned by ASSA ABLOY Entrance Systems or companies with in the ASSA ABLOY Group.

Q4.0-2015 © ASSA ABLOY Entrance Systems AB Technical data subject to change without notice.